



710 2T

High Performance 2 stroke engine lubricant

Lubrication by oil injector or premix

100% Synthetic – Ester – Anti-Smoke

TYPE OF USE

Any high performance 2 stroke bikes, sports bikes, replicas, trails, off road bikes, enduro, mopeds... fitted with high performance 2 stroke engines, running at high rpm in severe conditions, direct injection or carburetor.

Suitable for oil injector systems or premix, leaded or unleaded gasoline

Compatible with catalytic converters.

Other uses: Scooters, ATV...

PERFORMANCE

STANDARDS API TC – JASO FD - ISO-L-EGD
SPECIFICATIONS JASO FD under N°033MOT064

100% synthetic lubricant, Ester technology, specially engineered for high performance engines running at high rpm, perfect oil film resistance to protect against wear.

Improved power output, minimize engine internal friction.

Japanese JASO standard consists in passing 4 engine bench tests in order to evaluate lubricity, detergency, anti-smoke and anti-deposit lubricant properties. JASO FD performance is the highest level of JASO standard, improved engine cleanliness compared to JASO FC.

Formulation built on synthetic bases with very high combustion properties which minimize smoke and deposits.

Instantaneous and stable mixing with gasoline.

RECOMMENDATIONS

Mixing ratio: from 2% to 4% (from 50:1 to 25:1) according to manufacturers' requirements.

Adjust according to your own use.

PROPERTIES

| | | |
|----------------------------|------------|-------------------------|
| Color | Visual | Green |
| Density at 20°C (68°F) | ASTM D1298 | 0.862 |
| Viscosity at 40°C (104°F) | ASTM D445 | 46.4 mm ² /s |
| Viscosity at 100°C (212°F) | ASTM D445 | 8.9 mm ² /s |
| Viscosity index | ASTM D2270 | 175 |
| Flash point | ASTM D92 | 88°C / 190.4°F |
| TBN | ASTM D2896 | 2.15 mg KOH/g |

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty. – Made in France

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel : 33 1 48 11 70 00 - Fax : 33 1 48 33 28 79. Web Site: www.motul.com

01/13