

Product Data

Go! 2T

Trouble-Free Ride

Description

Castrol Go! 2T is a high quality engine oil designed for 2-stroke motorcycles, all-terrain vehicles, scooters and lawn equipment. It's Deposit Control Formula is designed for a trouble-free ride time after time.

Application

Exceeds industry specifications JASO FB standards

Advantages

Deposit Control Formula:

- · Protects against the build-up of carbon deposits on the piston and spark plug
- Enables fast and reliable starting
- Visibly reduces exhaust smoke in comparison with conventional mineral oils

Suitable for use with all makes of 2-stroke motorcycles, scooters, all-terrain vehicles and lawn equipment.

Always follow the vehicle manufacturer's recommendations.

Can be used in oil injection and in pre-mix with mixing ratios up to 50:1.

Typical Characteristics

Name	Method	Units	Typical Values
Density @ 15C, Relative	ASTM D4052	g/ml	0.880
Viscosity, Kinematic 100C	ASTM D445	mm²/s	11.0
Viscosity, Kinematic 40C	ASTM D445	mm²/s	94
Flash Point, PMCC	ASTM D93	°C	194

Product Performance Claims JASO FB

Go! 2T 30 Nov 2015 Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470 Telephone: 1,800.462.0835

www.castrol.com/us Email: contactus@bp.com