







# SAFETY DATA SHEET

Product Name:	PPE			
Pro Honda HP2 2-Stroke Synthetic Racing Oil, 12 x 16oz. Cas				

Revision Date: 16-Apr-2015

Revision Number: 1

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

### 1.1 Product Identifier

**Product Name:** Pro Honda HP2 2-Stroke Synthetic Racing Oil, 12 x 16oz. Cas

#### Other means of identification

**Product Code:** 2202-055

**Synonyms:** Not available

### 1.2 Recommended use of the chemical and restrictions on use

**Recommended Use:** Motorcycle Lubrication

**Uses advised against:** No information available

### 1.3. Details of the supplier of the safety data sheet

**Manufactured by:** Idemitsu Lubricants America Corporation  
701 Port Rd.  
Jeffersonville, IN. 47130  
Telephone: 812-285-8234  
Fax: 812-285-8243  
Contact Name: Robin Hutchens  
Email: sds@ilacorp.com

**24 Hour Emergency Phone Number:** Within USA and Canada: 1-800-424-9300  
Outside USA and Canada: + 1 703-741-5970 (collect calls accepted)

**2. HAZARDS IDENTIFICATION**

**2.1 Classification**

This material is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) and WHMIS 2015

Acute toxicity - Oral	Not classified
Acute toxicity - Dermal	Not classified
Acute toxicity - Inhalation (Gases)	Not classified
Acute toxicity - Inhalation (Vapors)	Not classified
Acute toxicity - Inhalation (Dusts/Mists)	Not classified
Skin corrosion/irritation	Not classified
Serious eye damage/eye irritation	Not classified
Respiratory sensitization	Not classified
Skin sensitization	Not classified
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Category 2 Testes
Specific target organ toxicity (single exposure)	Not classified
Specific target organ toxicity (repeated exposure)	Not classified
Aspiration toxicity	Not classified
Physical hazards	None

**2.2. Label elements**



**Signal word**

**Warning**

**Hazard statements**

H361 - Suspected of damaging fertility or the unborn child if swallowed

**Precautionary Statements - Prevention:**

P201 - Obtain special instructions before use  
 P202 - Do not handle until all safety precautions have been read and understood  
 P280 - Wear protective gloves/protective clothing/eye protection/face protection

**Precautionary Statements - Response:**

P308 + P313 - IF exposed or concerned: Get medical advice/attention

**Precautionary Statements - Storage:**

P405 - Store locked up

**Precautionary Statements - Disposal:**

P501 - Dispose of contents/ container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

Not applicable

**2.3 Other information**

**Other hazards**

- Causes mild skin irritation
- May cause long lasting harmful effects to aquatic life

Unknown acute toxicity

58.087% of the mixture consists of ingredient(s) of unknown toxicity

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Substances

Not applicable

#### 3.2 Mixtures

##### Hazardous components

Chemical Name	CAS-No	Weight %	Notes
Polyolefin alkyl phenol alkyl amine	Confidential	1-5	
Solvent naphtha (petroleum), light aromatic	64742-95-6	1-5	P
Tricresylphosphate	1330-78-5	1-5	

##### Components that do not contribute to this product's hazards

Chemical Name	CAS-No	Weight %
Synthetic Lubricant	Mixture	70-90
Lubricating Base Stocks	Mixture	1-10

### 4. FIRST AID MEASURES

#### 4.1 First Aid Measures

##### General Advice

If symptoms persist, call a physician. Get medical advice/attention if you feel unwell. Take a copy of the Safety Data Sheet when going for medical treatment.

##### Eye Contact

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.

##### Skin Contact

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

##### Inhalation

Move to fresh air in case of accidental inhalation of vapors. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Call a physician immediately.

##### Ingestion

Do not induce vomiting without medical advice. If vomiting occurs naturally, have casualty lean forward to reduce the risk of aspiration. Call a physician or Poison Control Center immediately.

##### Protection of First-aiders

Use personal protective equipment. Avoid contact with skin, eyes and clothing.

#### 4.2 Most important symptoms and effects, both acute and delayed

##### Symptoms

No information available.

#### 4.3 Indication of any immediate medical attention and special treatment needed

##### Notes to Physician

Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

Flammable Properties

NFPA: Class IIIB Combustible Liquid

**5.1 Suitable Extinguishing Media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment

**Unsuitable Extinguishing Media**

No information available.

**5.2 Specific Hazards Arising from the Chemical**

Keep product and empty container away from heat and sources of ignition.

**Hazardous combustion products:**

During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and / or irritating. Combustion products may include and are not limited to, Carbon oxides, Calcium Oxides (CaOx), Nitrogen oxides (NOx), Oxides of Phosphorus.

**5.3 Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**6. ACCIDENTAL RELEASE MEASURES**

**6.1 Personal precautions, protective equipment and emergency procedures**

**Personal precautions**

Avoid contact with the skin and the eyes. Use personal protective equipment. Remove all sources of ignition. Avoid breathing vapors or mists. Ensure adequate ventilation.

**6.2 Environmental Precautions**

**Environmental Precautions**

Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not allow material to contaminate ground water system. Do not flush into surface water or sanitary sewer system. Large Spills: Dike far ahead of liquid spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas.

**6.3 Methods and material for containment and cleaning up**

**Methods for Clean-up**

Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

**Spill Management**

**LARGE SPILLS**

Eliminate sources of ignition. Prevent additional discharge of material if possible to do so without hazard. For small spills implement cleanup procedures; for large spills implement cleanup procedures and, if in public area, keep public away and advise authorities. Also, if this product is subject to CERCLA reporting (see Section 15 Regulatory Information) notify the National Response Center.

**WATER SPILLS**

Prevent liquid entering sewers, watercourses, or low areas. Contain spilled liquid with sand or earth. Recover by pumping or with suitable absorbent. If liquid is too viscous for pumping, scrape up. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

**7. HANDLING AND STORAGE**

**7.1. Precautions for safe handling**

**Handling** Use only in area provided with appropriate exhaust ventilation. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Keep away from heat, sparks and open flame; No smoking. Wear personal protective equipment. Do not breathe vapors or spray mist. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).

**Safe Handling Advice** Wear personal protective equipment. Do not breathe vapors or spray mist. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).

**7.2. Conditions for safe storage, including any incompatibilities**

**Storage** Keep container tightly closed in a dry and well-ventilated place. Keep away from heat. Protect from light. Keep in properly labeled containers.

**Technical measures/Precautions** To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

**Incompatible Materials and/or Coatings** No information available

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters**

**Exposure Guidelines** This product does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies.

**Other Exposure Guidelines (If Generated)**

Chemical Name	OSHA PEL	ACGIH TLV	ACGIH OEL (STEL)	NIOSHT REL TWA	ILA IHG	ILA ROEG	ILA Internal Exposure Limit
Oil mist, mineral	TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>		TWA 5 mg/m <sup>3</sup> ST 10 mg/m <sup>3</sup>			

**8.2. Exposure controls**

**Appropriate engineering controls** Ensure adequate ventilation, especially in confined areas. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

**Personal Protective Equipment**

**Eye/face protection** Tightly fitting safety goggles. Wear chemical splash goggles and face shield when eye and face contact is possible due to splashing or spraying of material.

**Skin protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate to prevent skin contact. **Glove Type:** Neoprene, Nitriles.

**Respiratory protection**

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

**General Hygiene Considerations**

When using, do not eat, drink or smoke. Clean equipment, work area and clothing regularly. Remove and wash contaminated clothing before re-use.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

9.1. Information on basic physical and chemical properties

Appearance	Dark Blue
Physical State	Liquid
Odor	Mild
Odor Threshold	No information available
pH	Not applicable
Melting point / melting range	Not applicable
Boiling point / boiling range	No information available
Flash Point	105 °C / 221 °F SETA ASTM D3278
Evaporation Rate	No information available
Flammability Limit in Air	No information available
Explosion Limits	No information available
Vapor Pressure	No information available
Vapor Density (Air)	No information available
Density	0.94 g/cm <sup>3</sup> @15°C
Solubility	No information available
Partition Coefficient (n-octanol/water)	No information available
Autoignition Temperature	No information available
Decomposing Temperature	No information available
Viscosity	@ 40C = 167.40 cSt; @ 100C = 17.79 cSt

Other Information

**10. STABILITY AND REACTIVITY**

10.1 Reactivity

**Reactivity** The product is chemically stable

10.2 Chemical stability

**Chemical Stability** Stable under recommended storage conditions.

10.3 Possibility of Hazardous Reactions

**Possibility of Hazardous Reactions** None under normal processing.

**Hazardous Polymerization** Hazardous polymerisation does not occur.

10.4 Conditions to Avoid

**Conditions to Avoid** Heat, flames and sparks.

10.5 Incompatible Materials

**Incompatible Materials** Strong oxidizing agents.



The following values are calculated based on chapter 3.1 of the GHS document .

Product Information (Estimated):

ATEmix (oral)	> 5,000 mg/kg
ATEmix (dermal)	> 2,000 mg/kg
ATEmix (inhalation-dust/mist)	> 5 mg/l
ATEmix (inhalation-vapor)	> 20 mg/l

**12. ECOLOGICAL INFORMATION**

12.1 Ecotoxicity

**Ecotoxicity effects**

Harmful to aquatic life with long lasting effects. Plants and animals may experience harmful or fatal effects when coated with petroleum products. Petroleum-based (mineral) lubricating oils normally will float on water. In stagnant or slow-flowing waterways, an oil layer can cover a large surface area. As a result, this oil layer might limit or eliminate natural atmospheric oxygen transport into the water. With time, if not removed, oxygen depletion in the waterway may be sufficient to cause a fish kill or create an anaerobic environment.

**Unknown aquatic toxicity**

92.7741% of the mixture consists of component(s) of unknown hazards to the aquatic environment

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulation/Accumulation

No information available

12.4. Mobility in soil

No information available

PBT and vPvB assessment

No information available

12.5 Other adverse effects:

No information available

**13. DISPOSAL CONSIDERATIONS**

**Hazard characteristic and regulatory waste stream classification can change with product use. Accordingly, it is the responsibility of the user to determine the proper storage, transportation, treatment and/or disposal methodologies for spent materials and residues at the time of disposition.**

**To minimize exposure, see Section 8 (Exposure Controls/Personal Protection) of the SDS.**

**Waste Disposal Method**

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

**Contaminated packaging**

Dispose of in accordance with local regulations.

**14. TRANSPORT INFORMATION**

DOT

Not regulated

IATA

Not regulated



**IMDG/IMO**

Not regulated

**15. REGULATORY INFORMATION**

**International Inventories**

<b>TSCA</b>	All ingredients are on the inventory or exempt from listing
<b>DSL</b>	Not all ingredients are listed on the DSL Inventory List
<b>NDSL</b>	Not Listed
<b>EINECS</b>	Does not comply
<b>ELINCS</b>	Not Listed
<b>ENCS</b>	Does not comply
<b>CHINA</b>	All ingredients are on the inventory or exempt from listing
<b>KECL</b>	All ingredients are on the inventory or exempt from listing
<b>PICCS</b>	Does not comply
<b>AICS</b>	All ingredients are on the inventory or exempt from listing
<b>NZIoC</b>	Does not comply
<b>Mexico (INSQ)</b>	Does not comply

**USA**

**Federal Regulations**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

**SARA 311/312 Hazardous Categorization**

<b>Acute Health Hazard</b>	Yes
<b>Chronic Health Hazard</b>	Yes
<b>Fire Hazard</b>	No
<b>Sudden Release of Pressure Hazard</b>	No
<b>Reactive Hazard</b>	No

**CERCLA/SARA 302 & 304**

Section 302 & 304 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 355.

Chemical Name	CAS-No	Weight %	RQ	TPQ
Xylenes (o-, m-, p-isomers)	1330-20-7	<1	100 lb final RQ 45.4 kg final RQ	
Cumene	98-82-8	<1	5000 lb final RQ 2270 kg final RQ	
Ethyl benzene	100-41-4	<0.05	1000 lb final RQ 454 kg final RQ	
Styrene	100-42-5	<0.001	1000 lb final RQ 454 kg final RQ	
Toluene	108-88-3	<0.001	1000 lb final RQ 454 kg final RQ	
Benzene	71-43-2	<0.001	10 lb final RQ 4.54 kg final RQ	
Naphthalene	91-20-3	<0.001	100 lb final RQ 45.4 kg final RQ	

**Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)**

This product contains the following HAPs:

Chemical Name	CAS-No	Weight %	HAPS data
Xylenes (o-, m-, p- isomers)	1330-20-7	<1	X
Cumene	98-82-8	<1	X
Ethyl benzene	100-41-4	<0.05	X
Styrene	100-42-5	<0.001	X
Toluene	108-88-3	<0.001	X
Benzene	71-43-2	<0.001	X
Naphthalene	91-20-3	<0.001	X

**State Regulations**

**California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm

Chemical Name	CAS-No	Weight %	California Prop. 65	Maximum Allowable Dose for Reproductive Toxicity (MADLS)	Safe Harbor Limits for Cancer-causing Chemicals (NSRLs)
Cumene	98-82-8	<1	Carcinogen		
Ethyl benzene	100-41-4	<0.05	Carcinogen		54 µg/day inhalation 41 µg/day oral
Toluene	108-88-3	<0.001	Developmental Female Reproductive	7000µg/daylevel represents absorbed dose	
Benzene	71-43-2	<0.001	Carcinogen Developmental Male Reproductive	24µg/dayoral 49µg/dayinhalation	6.4 µg/day oral 13 µg/day inhalation
Naphthalene	91-20-3	<0.001	Carcinogen		5.8 µg/day

**State Right-to-Know**

Chemical Name	CAS-No	New Jersey
Tricresylphosphate	1330-78-5	X
Petroleum distillates, solvent-refined heavy paraffinic	64741-88-4	X
Xylenes (o-, m-, p- isomers)	1330-20-7	X
Propyl benzene	103-65-1	X
Cumene	98-82-8	X

**New Jersey Worker and Community Right-to-Know Act:**

Under the New Jersey Right-to-Know Act L. 1983 Chapter 315 N.J.S.A. 34:5A-1 et. seq., the product is to be identified as follows:  
PETROLEUM OIL (Lubricating Oil)

**Canada**

This material has been classified in accordance with the WHMIS 2015 regulation


Chemical Name	CAS-No	Weight %	NPRI
Solvent naphtha (petroleum), light aromatic	64742-95-6	1-5	Listed
Petroleum distillates, hydrotreated light	64742-47-8	<1	Listed

Pseudocumene	95-63-6	<1	Listed
Stoddard solvent	8052-41-3	<1	Listed
Cumene	98-82-8	<1	Listed
Xylenes (o-, m-, p- isomers)	1330-20-7	<1	Listed
1,3,5-Trimethylbenzene	108-67-8	<1	Listed
Ethyl benzene	100-41-4	<0.05	Listed
Styrene	100-42-5	<0.001	Listed
Toluene	108-88-3	<0.001	Listed
Benzene	71-43-2	<0.001	Listed
Naphthalene	91-20-3	<0.001	Listed

**Legend**

NPRI - National Pollutant Release Inventory

**16. OTHER INFORMATION**



NFPA

Health: 1

Flammability: 1

Instability 0

Prepared By  
Revision Date:

Susie Bibb  
16-Apr-2015

Revision Summary:

GHS SDS format

**Disclaimer:**

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet**