



2-STROKE SYNTHETIC LUBRICANT

Motorcycle TechniPlate® TC-W3

Klotz sets the standard for power and reliability. Motorcycle TechniPlate provides extreme high load carrying capacity for reduced engine wear. Clean Burn™ No-Smoke technology eliminates carbon and residue build-up. Warranty compliant for all major manufacturers including Yamaha®, Honda®, Suzuki®, Kawasaki®, and KTM®.

Klotz Motorcycle TechniPlate TC-W3 will challenge and outrun the competition in the following ways:

- **Improves throttle response**
- **TechniPlate® lubricity system for superior film strength and anti-scuff protection**
- **Clean Burn™ for low smoke and prevents plug fouling**
- **Keeps power valve clean**
- **Identifiable Klotz Red for easy mixing - Smells Like Klotz**
- **Fast, easy starting**
- **Pre-mix or oil injection**

CHARACTERISTICS

Smoke Rating	10	Scale 1 = Fog - 10 = No Smoke
Clean Burn™	10	Scale 1 = Heavy Deposits - 10 = No Carbon
Film Strength	8	Scale 1 = Failure - 10 = No Wear
Pour Point	-36°F	
Flash Point	275°F	
Maximum RPM	10,000	
Viscosity @ 100°C	7.10 cSt Typical	
Product Color	Red	
Chemical	100% Pure Synthetic	
Biodegradable	48%	

CERTIFICATIONS

API TC	TC-W	NMMA TC-W3
JASO FD	ISO-EGD	RL#93101

DIRECTIONS

Pre-mix 20:1 to 50:1
Refer to engine manufacturer's recommendation

COMPATIBILITY

Gasoline
*Stays in suspension
Fuel Stability: Will blend in gasoline at ratios of 15:1 or greater
Blends with petroleum and most synthetic oils



PART NUMBERS

KL-302	10 QT CASE
KL-302 30 GL	30 GAL DRUM
KL-302 55 GL	55 GAL DRUM

RECOMMENDED APPLICATIONS

2-Stroke Motorcycle

Stock
Street
Hi-Performance

2-Stroke Dirt Bike

Stock
Trail
Off-Road
Hi-Performance

Klotz Synthetic Lubricants
Fort Wayne, IN USA

Order Online: at klotzlube.com

Tech Line: 260.490.0489

Order Line: 800.242.0489

Email: salesteam@klotzlube.com

©2018 Klotz S.L., Inc Tech Sheet