

PRODUCT BULLETIN



Goldfire® Pro Synthetic Blend 2T Racing Premix Oil

Product Number	Net Contents	Units Per case
8-16	½ Liter	6
8-16-1L	1 Liter	5
8-16-1G	1 Gallon	2

PJ1 GOLDFIRE PRO 2-Stroke Racing Oil is designed for the serious racer who requires more efficient power for high revving greater horsepower 2-stroke engines. PJ1 uses only the highest grade of synthetics/petroleum oils with a special blend of additives to guard against piston scoring and cylinder wall scuffing as well as oxidation, and rust & corrosion. Provides less drag thereby improving throttle response, increasing power and allowing higher RPM.

APPLICATION AND PERFORMANCE:


- Designed for the serious racer.
- · Greatly extends the life of pistons and rings.
- Lengthens engine's life by improving lubrication at elevated temperatures.
- Extreme low coefficient of friction increases power and efficiency.
- Eliminates spark plug fouling, sticking power valves and carbon build-up.
- Protects against varnishing and sludge formation on critical engine parts.
- Inhibits rust, corrosion and oxidation.
 Meets and exceeds all manufacturers' warranty requirements.

GRAVITY API	<u>31.4</u>
POUNDS PER GALLON	7.23
VISCOSITY:	
ASTM D 2602 cST @ 40° C	42
ASTM D 445 cST @ -100° C	<u>7.1</u>
ASTM D 2161 SUS @ -100° F	<u>215</u>
VISCOSITY INDEX ASTM D 2270	128
VISUAL COLOR	PURPLE

LOW TEMPERATURE PUMPABILITY ASTM D 4684 TEMPERATURE °F (C°)

PERATURE °F (C°) -15(F) -25(C)

Warning: Mineral oils have been determined by the State of California to cause cancer.





8747 E. Via de Commercio/Scottsdale, AZ 85258 USA Phone 480-991-8002

Fax 480-991-8002

E-mail: Customer.service@pjhbrands.com







www.PJ1.com