

## Silkolene®

### SILKOLENE PRO 2

#### Ultimate Fully Synthetic Ester 2-Stroke Premix engine oil

##### Description

SILKOLENE PRO 2 is formulated using synthetic components including esters which provide the exceptional anti-seize properties usually only associated with castor-based oils. As well as the synthetic based SILKOLENE PRO 2 incorporates an advanced additive system to protect engine internals even at maximum revs.

Grand Prix experience has shown that SILKOLENE PRO 2 can provide racing engines with the outstanding load-carrying and lubrication requirements necessary for full power output even at high fuel to oil ratios. SILKOLENE PRO 2 uses aerospace technology to give the ultimate in engine protection, and maintains film strength at high temperatures, revs and stresses during motorcycle and kart racing.

SILKOLENE PRO 2 is particularly resistant to ring-sticking and plug fouling and helps to maintain maximum power for the track life of an engine. Special additives combat the problem of throttle sticking in wet conditions experienced with some types of racing carburettors. SILKOLENE PRO 2 combats varnish deposits on and below piston rings it also reduces carbon deposits on the piston crown and in the exhaust ports, giving more efficient ignition, essential when using the latest electronic power valve systems.

##### Application

SILKOLENE PRO 2 is recommended and developed primarily for two-stroke racing engines. It can be used successfully at 50:1 (2%) mixture although users should refer to engine manufacturers' instructions for their specific requirements.

SILKOLENE PRO 2 mixes easily with all types of standard pump fuel and high octane race fuels with no separation.

SILKOLENE PRO 2 must not be mixed with conventional two-stroke oils.  
Only for use as a Pre-Mix

##### Advantages

- Suitable for use in on-road, off-road and karting engines
- Ultimate engine protection under full race conditions
- Increased power performance and reliability
- Excellent load carrying capability and wear protection
- Maintains engine cleanliness

##### Specifications

- SILKOLENE PRO 2 is a CIK-FIA approved (homologated) lubricant.

# Product Information



## Further Information

### Typical Data: SILKOLENE PRO 2

Characteristics	Test Method	Unit	
SAE			40
Specific Gravity at 15°C	IP160		0.916
Kinematic Viscosity @ 100°C	IP71	mm <sup>2</sup> /s	13.1
Kinematic Viscosity @ 40°C	IP71	mm <sup>2</sup> /s	92.8
Viscosity Index	IP226		140
Flash Point (Closed Cup)	IP34	°C	184
Pour Point	IP15	°C	-48

Updated 25/01/2022 ABUK

FUCHS LUBRICANTS (UK) plc  
New Century Street, Hanley  
Stoke-on-Trent, Staffordshire, ST1 5HU

Tel +44 (0)1782 203700  
contact-uk@fuchs.com



Health, Safety and Environment - information is provided for products in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products.